According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY TM/MC FG PAG GEAR OIL 220

000003009245

Version 4.1 Revision Date 02.06.2025 Print Date 02.06.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : PURITY TM/MC FG PAG GEAR OIL 220

Product code : PFPG220P20, PFPG220DRX, PFPG220

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : PURITY FG PAG Gear Oils are used for high temperature Substance/Mixture

industrial gear applications for both H1 food grade and non-H1

industrial applications.

1.3 Details of the supplier of the safety data sheet

Manufacturer or supplier's details

Petro-Canada Europe Lubricants Limited

3rd Floor, 1 Ashley Road Altrincham Cheshire WA14 2DT

United Kingdom

Telephone : +44 (0) 121 781 7264

E-mail address of person

responsible for the SDS

: EUSDS@hfsinclair.com

1.4 Emergency telephone number

Emergency telephone : CHEMTREC: +1-703-741-5970;

number Poison Control Centre: Consult local telephone directory for

emergency number(s).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Long-term (chronic) aquatic hazard, H411: Toxic to aquatic life with long lasting effects.

Category 2

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY TM/MC FG PAG GEAR OIL 220

000003009245

Version 4.1 Revision Date 02.06.2025 Print Date 02.06.2025

Hazard pictograms :

*

Hazard statements : H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P273 Avoid release to the environment.

Response:

P391 Collect spillage.

Disposal:

P501 Dispose of contents/ container to an approved

waste disposal plant.

2.3 Other hazards

This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Benzenamine, N-phenyl-, reaction	68411-46-1	Aquatic Chronic 3;	0.25 - 1
products with 2,4,4- trimethylpentene	270-128-1	H412 Repr. 2; H361f	
O,O,O-triphenyl phosphorothioate	597-82-0 209-909-9	Aquatic Chronic 1; H410	0.25 - 1
		M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 10	
N-methyl-N-[C18- (unsaturated)alkanoyl]glycine	701-177-3	Acute Tox. 4; H332 Skin irr. 2; H315 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 3; H412	0.25 - 1

For explanation of abbreviations see section 16.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY TM/MC FG PAG GEAR OIL 220

000003009245

Version 4.1 Revision Date 02.06.2025 Print Date 02.06.2025

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled Move to fresh air.

Artificial respiration and/or oxygen may be necessary.

Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Wash clothing before reuse.

Seek medical advice.

Remove contact lenses. In case of eye contact

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Obtain medical attention.

If swallowed Rinse mouth with water.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

Seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Risks : First aider needs to protect himself.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: No information available.

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Cool closed containers exposed to fire with water spray.

Hazardous combustion

Carbon oxides (CO, CO2), smoke and irritating vapours as

products

products of incomplete combustion.

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

Page: 3 / 15

Petro-Canada Lubricants is an HF Sinclair brand

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY TM/MC FG PAG GEAR OIL 220

000003009245

Version 4.1 Revision Date 02.06.2025 Print Date 02.06.2025

5.3 Advice for firefighters

Further information : Prevent fire extinguishing water from contaminating surface

water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Ensure adequate ventilation.
Evacuate personnel to safe areas.
Material can create slippery conditions.

Mark the contaminated area with signs and prevent access to

unauthorized personnel.

Only qualified personnel equipped with suitable protective

equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the

environment.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Prevent further leakage or spillage if safe to do so.

Remove all sources of ignition.
Soak up with inert absorbent material.
Non-sparking tools should be used.
Ensure adequate ventilation.
Contact the proper local authorities.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Use only with adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin, eyes and clothing.

Do not ingest.

Keep away from heat and sources of ignition. Keep container closed when not in use.

Advice on protection against : None known.

Internet: www.petrocanadalubricants.com/sds

Trademarks are owned or used under license.

Page: 4 / 15 Petro-Canada Lubricants is an HF Sinclair brand

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY TM/MC FG PAG GEAR OIL 220

000003009245

Version 4.1 Revision Date 02.06.2025 Print Date 02.06.2025

fire and explosion

Hygiene measures : Remove and wash contaminated clothing and gloves,

including the inside, before re-use. Wash face, hands and any

exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store

in heat or direct sunlight.

7.3 Specific end use(s)

Specific use(s) : For further information see Section 1 of the safety data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

Eye/face protection : Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton®.

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is

necessary.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

Internet: www.petrocanadalubricants.com/sds

Page: 5 / 15 Petro-Canada Lubricants is an HF Sinclair brand

Trademarks are owned or used under license.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY TM/MC FG PAG GEAR OIL 220

000003009245

Version 4.1 Revision Date 02.06.2025 Print Date 02.06.2025

working limits of the selected respirator.

Filter type : organic vapour filter

Protective measures : Wash contaminated clothing before re-use.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : clear

Odour : mild

Odour Threshold : No data available

Pour point : -38 °C

Boiling point/boiling range : No data available

Flash point : 263 °C

Method: Cleveland open cup

pH : No data available

Fire Point : No data available

Auto-Ignition Temperature : No data available

Evaporation rate : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Density : 1.0775 kg/l (15 °C)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY TM/MC FG PAG GEAR OIL 220

000003009245

Version 4.1 Revision Date 02.06.2025 Print Date 02.06.2025

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : 220 cSt (40 °C)

38.4 cSt (100 °C)

Flammability : Low fire hazard. This material must be heated before ignition

will occur.

Explosive properties : Do not pressurize, cut, weld, braze, solder, drill, grind or

expose containers to heat or sources of ignition.

9.2 Other information

Particle size : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : Reactive with oxidising agents.

10.6 Hazardous decomposition products

Hazardous decomposition : May release COx, smoke and irritating vapours when heated

products to decomposition.

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY TM/MC FG PAG GEAR OIL 220

000003009245

Version 4.1 Revision Date 02.06.2025 Print Date 02.06.2025

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of:

exposure

Eye contact Ingestion Inhalation Skin contact

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Components:

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

O,O,O-triphenyl phosphorothioate:

Acute oral toxicity : LD50 (Rat): > 10,000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

N-methyl-N-[C18-(unsaturated)alkanoyl]glycine:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1.37 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

Page: 8 / 15 Petro-Canada Lubricants is an HF Sinclair brand

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY TM/MC FG PAG GEAR OIL 220

000003009245

Version 4.1 Revision Date 02.06.2025 Print Date 02.06.2025

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish Remarks: No data available

Toxicity to daphnia and other : Remarks: No data available

aquatic invertebrates

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms

Remarks: No data available

Components:

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l Toxicity to fish

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 51 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l

Exposure time: 72 h

O,O,O-triphenyl phosphorothioate:

Toxicity to fish LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY TM/MC FG PAG GEAR OIL 220

000003009245

Version 4.1 Revision Date 02.06.2025 Print Date 02.06.2025

Toxicity to algae/aquatic

plants

: EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l

Exposure time: 72 h

M-Factor (Acute aquatic

toxicity)

: 1

Toxicity to fish (Chronic

toxicity)

: NOEC: 0.0017 mg/l Exposure time: 97 d

Species: Oncorhynchus mykiss (rainbow trout)

M-Factor (Chronic aquatic

toxicity)

: 10

N-methyl-N-[C18-(unsaturated)alkanoyl]glycine:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 0.43 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 0.43 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): 6.3 mg/l

Exposure time: 72 h

NOEC (Desmodesmus subspicatus (green algae)): 0.91 mg/l

Exposure time: 72 h

12.2 Persistence and degradability

Product:

: Remarks: No data available Biodegradability

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

This substance/mixture contains components considered to Assessment

be either persistent, bioaccumulative and toxic (PBT), or very

persistent and very bioaccumulative (vPvB).

Components:

O,O,O-triphenyl phosphorothioate:

Assessment : PBT substance

12.6 Other adverse effects

Product:

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

Page: 10 / 15 Petro-Canada Lubricants is an HF Sinclair brand

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY TM/MC FG PAG GEAR OIL 220

000003009245

Version 4.1 Revision Date 02.06.2025 Print Date 02.06.2025

Endocrine disrupting

potential

: This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Offer surplus and non-recyclable solutions to a licensed

disposal company.

Waste must be classified and labelled prior to recycling or

disposal.

Send to a licensed waste management company.

Dispose of product residue in accordance with the instructions

of the person responsible for waste disposal.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 3082
ADR : UN 3082
RID : UN 3082
IMDG : UN 3082
IATA (Cargo) : UN 3082

14.2 UN proper shipping name

ADN : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(O,O,O-triphenyl phosphorothioate)

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S

(O,O,O-triphenyl phosphorothioate)

RID : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(O,O,O-triphenyl phosphorothioate)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(O,O,O-triphenyl phosphorothioate)

IATA (Cargo) : Environmentally hazardous substance, liquid, n.o.s.

(O,O,O-triphenyl phosphorothioate)

14.3 Transport hazard class(es)

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY TM/MC FG PAG GEAR OIL 220

000003009245

Version 4.1 Revision Date 02.06.2025 Print Date 02.06.2025

Class Subsidiary risks

ADN : 9

ADR : 9

RID : 9

IMDG : 9

IATA (Cargo) : 9

14.4 Packing group

ADN

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

ADR

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

RID

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

IMDG

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo : 964

aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY TM/MC FG PAG GEAR OIL 220

000003009245

Version 4.1 Revision Date 02.06.2025 Print Date 02.06.2025

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

: Not applicable

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great

Britain)

: Not applicable

Regulation (EU) No 2024/590 on substances that

deplete the ozone layer

: Not applicable

UK REACH List of substances subject to authorisation :

(Annex XIV)

: Not applicable

The components of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

IECSC : On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY TM/MC FG PAG GEAR OIL 220

000003009245

Version 4.1 Revision Date 02.06.2025 Print Date 02.06.2025

SECTION 16: Other information

Full text of H-Statements

H315 : Causes skin irritation.

H318 : Causes serious eye damage.

H332 : Harmful if inhaled.

H361f : Suspected of damaging fertility.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Eye Dam. : Serious eye damage/eye irritation

Repr. : Reproductive toxicity
Skin irr. : Skin corrosion/irritation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan): ErCx -Concentration associated with x% growth rate response: GHS - Globally Harmonized System: GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

Page: 14 / 15 Petro-Canada Lubricants is an HF Sinclair brand

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY TM/MC FG PAG GEAR OIL 220

000003009245

Version 4.1 Revision Date 02.06.2025 Print Date 02.06.2025

Further information

For Copy of SDS : Internet: www.petrocanadalubricants.com/sds

Order Email for packed goods: pcepackage@hfsinclair.com

Order Email for bulk: pceorders@hfsinclair.com Telephone: +31 88313 0365 / +31 88313 0366 For Product Safety Information: 1 905-491-0565

Prepared by : Product Safety: +1 905-491-0565

Classification of the mixture: Classification procedure:

Aquatic Chronic 2 H411 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB/EN