

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



PURITY™ FG SYNTHETIC EP GEAR FLUID 460

000003000548

Version 7.0

Revision Date 25.04.2025

Print Date 25.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : PURITY™ FG SYNTHETIC EP GEAR FLUID 460

Product code : PFSN460DRX, PFSN460P20, PFSN460

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : PURITY FG Synthetic EP Gear Fluid 460 is a food grade lub-
ricant.

NSF H1 Registered.

This product complies with FDA 21 CFR 178.3570 "Lubricants with Incidental Food Contact". It is intended for application on industrial and food equipment. It should not be added directly to the food product.

1.3 Details of the supplier of the safety data sheet

Manufacturer or supplier's details

Petro-Canada Europe Lubricants Limited
3rd Floor, 1 Ashley Road
Altrincham Cheshire WA14 2DT
United Kingdom

Telephone : +44 (0) 121 781 7264

E-mail address of person
responsible for the SDS : EUSDS@hfsinclair.com

1.4 Emergency telephone number

Emergency telephone num-
ber : CHEMTREC: +1-703-741-5970;
Poison Control Centre: Consult local telephone directory for
emergency number(s).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK
SI 2019/720, and UK SI 2020/1567)**

Long-term (chronic) aquatic hazard, Cat-
egory 2 H411: Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



PURITY™ FG SYNTHETIC EP GEAR FLUID 460

000003000548

Version 7.0

Revision Date 25.04.2025

Print Date 25.04.2025

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :



Hazard statements : H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

P273 Avoid release to the environment.

Response:

P391 Collect spillage.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2,6-di-tert-butyl-p-cresol	128-37-0 204-881-4	Aquatic Chronic 1; H410 Aquatic Acute 1; H400	0.25 - 1
O,O,O-triphenyl phosphorothioate	597-82-0 209-909-9	Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 10	0.25 - 1
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1 270-128-1	Aquatic Chronic 3; H412 Repr. 2; H361f	0.1 - 0.25

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



PURITY™ FG SYNTHETIC EP GEAR FLUID 460

000003000548

Version 7.0

Revision Date 25.04.2025

Print Date 25.04.2025

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- | | | |
|-------------------------|---|---|
| If inhaled | : | Move to fresh air.
Artificial respiration and/or oxygen may be necessary.
Seek medical advice. |
| In case of skin contact | : | In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Wash skin thoroughly with soap and water or use recognized skin cleanser.
Wash clothing before reuse.
Seek medical advice. |
| In case of eye contact | : | Remove contact lenses.
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Obtain medical attention. |
| If swallowed | : | Rinse mouth with water.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Never give anything by mouth to an unconscious person.
Seek medical advice. |

4.2 Most important symptoms and effects, both acute and delayed

- | | | |
|-------|---|---------------------------------------|
| Risks | : | First aider needs to protect himself. |
|-------|---|---------------------------------------|

4.3 Indication of any immediate medical attention and special treatment needed

- | | | |
|-----------|---|------------------------|
| Treatment | : | Treat symptomatically. |
|-----------|---|------------------------|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | | |
|--------------------------------|---|---|
| Suitable extinguishing media | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Unsuitable extinguishing media | : | No information available. |

5.2 Special hazards arising from the substance or mixture

- | | | |
|---------------------------------------|---|--|
| Specific hazards during fire-fighting | : | Cool closed containers exposed to fire with water spray. |
|---------------------------------------|---|--|

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



PURITY™ FG SYNTHETIC EP GEAR FLUID 460

000003000548

Version 7.0

Revision Date 25.04.2025

Print Date 25.04.2025

Hazardous combustion products : Carbon oxides (CO, CO₂), silicon oxides (SiO_x), smoke and irritating vapours as products of incomplete combustion.

5.3 Advice for firefighters

Further information : Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Evacuate personnel to safe areas.
Material can create slippery conditions.
Mark the contaminated area with signs and prevent access to unauthorized personnel.
Only qualified personnel equipped with suitable protective equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Prevent further leakage or spillage if safe to do so.
Remove all sources of ignition.
Soak up with inert absorbent material.
Non-sparking tools should be used.
Ensure adequate ventilation.
Contact the proper local authorities.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Use only with adequate ventilation.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin, eyes and clothing.
Do not ingest.
Keep away from heat and sources of ignition.
Keep container closed when not in use.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY™ FG SYNTHETIC EP GEAR FLUID 460

000003000548

Version 7.0

Revision Date 25.04.2025

Print Date 25.04.2025

Advice on protection against fire and explosion : None known.

Hygiene measures : Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sunlight.

7.3 Specific end use(s)

Specific use(s) : For further information see Section 1 of the safety data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2,6-di-tert-butyl-p-cresol	128-37-0	TWA	10 mg/m3	GB EH40

8.2 Exposure controls

Engineering measures

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

Eye/face protection : Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton®.

Remarks

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Skin and body protection

: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



PURITY™ FG SYNTHETIC EP GEAR FLUID 460

000003000548

Version 7.0

Revision Date 25.04.2025

Print Date 25.04.2025

Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Filter type	:	organic vapour filter
Protective measures	:	Wash contaminated clothing before re-use.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	colourless
Odour	:	mild
Odour Threshold	:	No data available
Pour point	:	-42 °C
Boiling point/boiling range	:	No data available
Flash point	:	253 °C Method: Cleveland open cup
pH	:	No data available
Fire Point	:	No data available
Auto-Ignition Temperature	:	No data available
Evaporation rate	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



PURITY™ FG SYNTHETIC EP GEAR FLUID 460

000003000548

Version 7.0

Revision Date 25.04.2025

Print Date 25.04.2025

Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.8524 kg/l (15 °C)
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	446 cSt (40 °C) 43.5 cSt (100 °C)
Flammability	:	Low fire hazard. This material must be heated before ignition will occur.
Explosive properties	:	Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

9.2 Other information

Particle size	:	No data available
---------------	---	-------------------

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Conditions to avoid : No data available

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



PURITY™ FG SYNTHETIC EP GEAR FLUID 460

000003000548

Version 7.0

Revision Date 25.04.2025

Print Date 25.04.2025

10.5 Incompatible materials

Materials to avoid : Reactive with oxidising agents, acids and alkalis.

10.6 Hazardous decomposition products

Hazardous decomposition products : May release CO_x, NO_x, SO_x, PO_x, formaldehyde, smoke and irritating vapours when heated to decomposition.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Eye contact
Ingestion
Inhalation
Skin contact

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Components:

O,O,O-triphenyl phosphorothioate:

Acute oral toxicity : LD50 (Rat): > 10,000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY™ FG SYNTHETIC EP GEAR FLUID 460

000003000548

Version 7.0

Revision Date 25.04.2025

Print Date 25.04.2025

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

O,O,O-triphenyl phosphorothioate:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 1

Toxicity to fish (Chronic tox-) : NOEC: 0.0017 mg/l

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



PURITY™ FG SYNTHETIC EP GEAR FLUID 460

000003000548

Version 7.0

Revision Date 25.04.2025

Print Date 25.04.2025

icity) Exposure time: 97 d
Species: Oncorhynchus mykiss (rainbow trout)

M-Factor (Chronic aquatic toxicity) : 10

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 51 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

Components:

O,O,O-triphenyl phosphorothioate:

Assessment : PBT substance

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Offer surplus and non-recyclable solutions to a licensed disposal company.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



PURITY™ FG SYNTHETIC EP GEAR FLUID 460

000003000548

Version 7.0

Revision Date 25.04.2025

Print Date 25.04.2025

Waste must be classified and labelled prior to recycling or disposal.
Send to a licensed waste management company.
Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 3082
ADR : UN 3082
RID : UN 3082
IMDG : UN 3082
IATA (Cargo) : UN 3082

14.2 UN proper shipping name

ADN : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(O,O,O-triphenyl phosphorothioate)
ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(O,O,O-triphenyl phosphorothioate)
RID : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(O,O,O-triphenyl phosphorothioate)
IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(O,O,O-triphenyl phosphorothioate)
IATA (Cargo) : Environmentally hazardous substance, liquid, n.o.s.
(O,O,O-triphenyl phosphorothioate)

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 9	
ADR	: 9	
RID	: 9	
IMDG	: 9	
IATA (Cargo)	: 9	

14.4 Packing group

ADN
Packing group : III

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



PURITY™ FG SYNTHETIC EP GEAR FLUID 460

000003000548

Version 7.0

Revision Date 25.04.2025

Print Date 25.04.2025

Classification Code : M6
Hazard Identification Number : 90
Labels : 9

ADR

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

RID

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

IMDG

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



PURITY™ FG SYNTHETIC EP GEAR FLUID 460

000003000548

Version 7.0

Revision Date 25.04.2025

Print Date 25.04.2025

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

The components of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

IECSC : On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Full text of H-Statements

H361f : Suspected of damaging fertility.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Repr. : Reproductive toxicity
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



PURITY™ FG SYNTHETIC EP GEAR FLUID 460

000003000548

Version 7.0

Revision Date 25.04.2025

Print Date 25.04.2025

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

For Copy of SDS : Internet: www.petrocanadalubricants.com/sds
Order Email for packed goods: pcepackage@hfsinclair.com
Order Email for bulk: pceorders@hfsinclair.com
Telephone: +31 88313 0365 / +31 88313 0366
For Product Safety Information: 1 905-491-0565

Prepared by : Product Safety: +1 905-491-0565

Classification of the mixture:

Aquatic Chronic 2 H411

Classification procedure:

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



PURITY™ FG SYNTHETIC EP GEAR FLUID 460

000003000548

Version 7.0

Revision Date 25.04.2025

Print Date 25.04.2025

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN